11

Please add before paragraph [0008] the following new heading:

8 - 1.05 TM

## **BRIEF DESCRIPTION OF THE DRAWINGS**

Please add before paragraph [0017] the following heading:

## **DETAILED DESCRIPTION OF THE DRAWINGS**

Please replace paragraph [0017] with the following amended paragraph:

In Fig. 1, which shows a vertical section through a drying cabinet with a view of a cleaning device, a drying cabinet in its entirety is designated by 1. This a drying cabinet 1 comprises a housing cube 2 which is open on one side and which can be closed on the open side by a door 3. When the drying cabinet 1 is designed as a vacuum drying cabinet, a seal, not shown, is fastened to the door 3. The interior 4 of the drying cabinet 1 is designated by 4. This interior 4 is subdivided by heating plates 5 which are designed as shelves upon which product trays 6 can be placed. These product trays 6 are removable. Therefore, they can be cleaned outside of the drying cabinet 1 in a particularly efficient manner. Only one of the product trays 6, that on the topmost heating plate 5, is shown. All product trays 6 are removed from the drying cabinet 1 when cleaning work is performed on the drying cabinet 1; for this reason, the one product tray 6 is indicated in dashed lines to show its position. The bottom of the drying cabinet 1 can also contain a heating plate 5.